

View Online at <https://aerobasegroup.com/nsn/5320-01-043-7798>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.350 inches and 1.370 inches

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2540 inches and 0.2545 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Grip Length:

0.885 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Solid film and cetyl alcohol lubrication

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield 3, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0