

View Online at <https://aerobasegroup.com/nsn/5320-01-043-8096>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.741 inches and 0.761 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2540 inches and 0.2545 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.3948 inches

**Grip Length:**

0.385 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Solid film and cetyl alcohol lubrication

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Ti-shield 3, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0