# NSN 5320-01-044-2508

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-044-2508



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.183 inches and 1.208 inches

## Head Style:

Flush countersunk

#### Shank Diameter:

0.3547 inches

### Head Major Diameter:

0.522 inches

### Tip Diameter:

0.3410 inches

#### Lubrication:

Cetyl alcohol and dry film

## Grip Length:

Between 0.802 inches and 0.817 inches

## Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.312 inches

### Shear Strength:

95000 single pounds per square inch

### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

### Material:

Titanium alloy uns r56400

### **Material Specification:**

Ams 4928 assn standard single material response

### **Thread Series Designator:**

Unjf

### **Specification Data:**

80205-nas1725 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-044-2508

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

