# NSN 5320-01-044-3108

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-044-3108



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Identification Code Color:

Bronze

#### Fastener Length:

Between 1.240 inches and 1.260 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.037 inches and 0.047 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.242 inches and 0.262 inches

#### Grip Length:

0.943 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.164 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Cetyl alcohol lubrication, color bronze

#### Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

#### **Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military

specification 3rd material response or mil-s-6049 military specification 4th material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### Thread Series Designator:

Unjc

# NSN 5320-01-044-3108

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

## Mil-std (military Standard):

Mil-s-5000 spec.

