NSN 5320-01-044-3274

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-044-3274 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.697 inches and 0.722 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.2754 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.426 inches Tip Diameter: 0.2707 inches Lubrication: Cetyl alcohol and dry film **Grip Length:** Between 0.365 inches and 0.380 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1725 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

--

NSN 5320-01-044-3274

Pin-rivet - Page 2 of 2



Der	nilit	ariz	atio	n:

No

Fiig:

A528u0