NSN 5320-01-044-3279

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-044-3279



Thread Class:

3

Thread Direction:

Right-hand

Fastener Length:

Between 0.621 inches and 0.646 inches

Head Style:

Flush countersunk

Shank Diameter:

0.3403 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

0.508 inches

Tip Diameter:

0.3381 inches

Lubrication:

Cetyl alcohol and dry film

Grip Length:

Between 0.240 inches and 0.255 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1725 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-044-3279

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

