

View Online at <https://aerobasegroup.com/nsn/5320-01-044-5247>

Fastener Length:

0.730 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.311 inches and 0.312 inches

Shank Style:

Blind rivet, nut and bolt (assembly)

Head Major Diameter:

Between 0.3486 inches and 0.3536 inches

Expansion Device:

Threaded stem

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.220 inches and 0.281 inches

Shear Strength:

12500 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp e4340 sleeve or steel comp 4340 sleeve or steel comp 4140 sleeve

Material Specification:

Mil-s-5000 military specification 1st material response sleeve or mil-s-5000 military specification 2nd material response sleeve or mil-s-5626 military specification 3rd material response sleeve

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-18732 spec.