

View Online at <https://aerobasegroup.com/nsn/5320-01-044-5247>

**Fastener Length:**

0.730 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.311 inches and 0.312 inches

**Shank Style:**

Blind rivet, nut and bolt (assembly)

**Head Major Diameter:**

Between 0.3486 inches and 0.3536 inches

**Expansion Device:**

Threaded stem

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.220 inches and 0.281 inches

**Shear Strength:**

12500 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp e4340 sleeve or steel comp 4340 sleeve or steel comp 4140 sleeve

**Material Specification:**

Mil-s-5000 military specification 1st material response sleeve or mil-s-5000 military specification 2nd material response sleeve or mil-s-5626 military specification 3rd material response sleeve

**Surface Treatment:**

Passivate stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-18732 spec.