## NSN 5320-01-044-5346

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-044-5346



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.635 inches and 0.660 inches

## Head Style:

Flush countersunk

## Shank Diameter:

0.2313 inches

## Shank Style:

Pin-rivet, tapered, threaded

## Head Major Diameter:

0.348 inches

## Tip Diameter:

0.2276 inches

## Lubrication:

Cetyl alcohol and dry film

## Grip Length:

Between 0.302 inches and 0.317 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

160000 pounds per square inch

## **Thread Size:**

0.190 inches

## Shear Strength:

95000 single pounds per square inch

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-044-5346

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

