NSN 5320-01-044-5348

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-044-5348 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.750 inches and 0.785 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.2313 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.348 inches Tip Diameter: 0.225 inches Lubrication: Cetyl alcohol and dry film **Grip Length:** Between 0.427 inches and 0.442 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.19 She 950 Cou Betv Mat Tita Mat Ams Thr Unjf She N/a Uni

0.190 inches
Shear Strength:
95000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5320-01-044-5348

Pin-rivet - Page 2 of 2



Fiig:

A528u0