## NSN 5320-01-044-6609

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-044-6609 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.897 inches and 0.917 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1940 inches and 0.1945 inches **Shank Style: Head Major Diameter:** 0.3016 inches **Grip Length:** 0.572 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Solid film and cetyl alcohol lubrication Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response or tiodize type 2, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5320-01-044-6609

Pin-rivet - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A528u0