NSN 5320-01-044-8693

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-044-8693 **Head Style:** Hexagon countersunk **Head Height:** Between 0.067 inches and 0.074 inches Shank Diameter: Between 0.178 inches and 0.180 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem **Grip Length:** Between 0.407 inches and 0.469 inches Width Across Flats: Between 0.277 inches and 0.283 inches Hardness Rating: 39.0 rockwell c bolt and 43.0 rockwell c bolt **Countersink Angle:** 100.0 degrees **Special Features:** Body color green Material: Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium sleeve and chromate sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl2 federal specification single treatment response bolt and qq-p-35 federal specification 2nd treatment response bolt **Specification Data:** 80205-nas1754 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Mil-s-5626 spec.

Mil-std (military Standard):

Fiig: A040a0