NSN 5320-01-045-2506

Blind Rivet - Page 1 of 1

A040a0

Mil-s-5626 spec.

Mil-std (military Standard):



View Online at https://aerobasegroup.com/nsn/5320-01-045-2506 **Head Style:** Hexagon **Head Height:** 0.160 inches **Shank Diameter:** Between 0.325 inches and 0.327 inches Shank Style: Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem **Grip Length:** Between 0.282 inches and 0.344 inches Width Across Flats: Between 0.429 inches and 0.437 inches Hardness Rating: 39.0 rockwell c nut and 43.0 rockwell c nut Shear Strength: 10350 double pounds per square inch Material: Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response nut **Specification Data:** 80205-nas1753 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: