## NSN 5320-01-045-2523

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-045-2523 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.832 inches and 0.852 inches **Head Style:** Err-090 **Head Height:** Between 0.056 inches and 0.063 inches **Shank Diameter:** Between 0.2005 inches and 0.2025 inches **Shank Style:** Pin-rivet, multiple grooved **Head Major Diameter:** Between 0.288 inches and 0.302 inches **Grip Length:** Between 0.689 inches and 0.750 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.099 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 **Material Specification:** Mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5320-01-045-2523

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.