# NSN 5320-01-045-2535

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-045-2535



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.073 inches and 1.093 inches

## Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2646 inches and 0.2651 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

### Lubrication:

Cetyl alcohol

## Grip Length:

0.693 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

# Shear Strength:

125000 single pounds per square inch

# Material:

Steel comp xm-13

# Material Specification:

Ams 5629 assn standard single material response

## Surface Treatment:

Passivate

# Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 5320-01-045-2535

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

