NSN 5320-01-045-5607

Blind Rivet - Page 1 of 1

Fiig: A040a0

Mil-std (military Standard):

Mil-s-5626 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-045-5607 **Head Style:** Hexagon **Head Height:** 0.135 inches Shank Diameter: Between 0.258 inches and 0.260 inches Shank Style: Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem **Grip Length:** Between 1.157 inches and 1.219 inches Width Across Flats: Between 0.458 inches and 0.472 inches **Hardness Rating:** 39.0 rockwell c bolt and 43.0 rockwell c bolt **Special Features:** Body color green Material: Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium sleeve and chromate sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl2 federal specification 1st treatment response sleeve and qq-p-35 federal specification 2nd treatment response sleeve **Specification Data:** 80205-nas1673 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No