## NSN 5320-01-045-9632



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-045-9632 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.503 inches and 0.523 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol **End Application:** W/s: aircraft, eagle, f-15; aircraft, harrier av-8b **Grip Length:** 0.193 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-045-9632

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0