NSN 5320-01-046-0719

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-046-0719



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.690 inches and 0.710 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2021 inches and 0.2026 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.380 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

125000 single pounds per square inch

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-046-0719

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

