NSN 5320-01-046-3369

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-046-3369

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.677 inches and 0.697 inches
Head Style:
Err-090
Head Height:
Between 0.055 inches and 0.065 inches
Width Between Flats:
Between 0.0791 inches and 0.0801 inches
Shank Diameter:
Between 0.1625 inches and 0.1635 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.306 inches and 0.322 inches
Lubrication:
Cetyl alcohol
Grip Length:
0.380 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.164 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Top of head color blue
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response or ams 5731 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
11.2.

Unjc

NSN 5320-01-046-3369

Pin-rivet - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0