NSN 5320-01-048-3382



Blind Rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-048-3382 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.3090 inches and 0.3120 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** Between 0.4689 inches and 0.4739 inches **Expansion Device:** Threaded stem and expander **Grip Length:** 0.3750 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Furnished wihout bolt Material: Steel comp 305 sleeve **Material Specification:** Qq-s-763 federal specification single material response sleeve **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Demilitarization:

No

Unit Of Measure:

NSN 5320-01-048-3382

Blind Rivet - Page 2 of 2



Fiig:

A040a0