

View Online at <https://aerobasegroup.com/nsn/5320-01-049-2810>

**Fastener Length:**

0.795 inches

**Head Style:**

Hexagon

**Head Height:**

0.096 inches

**Shank Diameter:**

Between 0.161 inches and 0.162 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Threaded stem

**Grip Length:**

0.156 inches

**Width Across Flats:**

Between 0.244 inches and 0.250 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Shear Strength:**

3355 double pounds per square inch

**Material:**

Steel sleeve or steel comp 303 sleeve or steel comp 304 sleeve

**Material Specification:**

Mil-s-5626 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-6758 military specification 3rd material response stem

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.