

View Online at <https://aerobasegroup.com/nsn/5320-01-051-5910>

**Fastener Length:**

Between 0.802 inches and 0.817 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.201 inches and 0.203 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.386 inches

**Head Minor Diameter:**

0.078 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 1.001 inches and 1.062 inches

**Countersink Angle:**

100.0 degrees

**Special Features:**

Rivet designed to mate w/lock collar id maximum 0.164 in. And od maximum 0.200 in., collar surface treated per mil-c-5541, sleeve lubricated w/cetyl alcohol, head has 0.078 in. Hex socket

**Material:**

Steel body

**Material Specification:**

Fed standard 66, aisi/sae 8740 federal specification 1st material response body

**Surface Treatment:**

Cadmium body

**Surface Treatment Specification:**

Qq-p-416, tl 2, cl 3 federal specification single treatment response body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0