

View Online at <https://aerobasegroup.com/nsn/5320-01-051-5911>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.865 inches and 0.880 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.201 inches and 0.203 inches

Shank Style:

Err-090

Head Major Diameter:

0.386 inches

Head Minor Diameter:

0.078 inches

Grip Length:

Between 1.063 inches and 1.125 inches

Thready Qty Per Inch (tpi):

56

Thread Size:

0.203 inches

Countersink Angle:

100.0 degrees

Special Features:

Rivet designed to mate w/ lock collar id maximum 0.164 in. And od maximum 0.200 in. In., collar surface treated per mil-c-5541, sleeve lubricated w/ cetyl alcohol, head has 0.078 in. Hex socket

Material:

Steel body

Material Specification:

Fed standard 66, aisi/sae 8740 federal specification 1st material response body

Surface Treatment:

Cadmium body

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response body

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0