

View Online at <https://aerobasegroup.com/nsn/5320-01-052-5016>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.740 inches and 0.755 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.200 inches and 0.202 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

0.386 inches

**Head Minor Diameter:**

0.078 inches

**Grip Length:**

Between 0.939 inches and 1.000 inches

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.164 inches

**Countersink Angle:**

100.0 degrees

**Special Features:**

Rivet designed to mate w/ lock collar id maximum 0.164 in. And od maximum 0.200 in., collar surface treated per mil-c-5541, sleeve lubricated w/ cetyl alcohol, head has 0.078 in. Hex socket

**Material:**

Steel body

**Material Specification:**

Fed standard 66, aisi/sae 8740 federal specification 1st material response body

**Surface Treatment:**

Cadmium body

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response body

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0