

View Online at <https://aerobasegroup.com/nsn/5320-01-053-2932>

**Fastener Length:**

Between 0.253 inches and 0.295 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.123 inches and 0.128 inches

**Shank Style:**

Self-plugging

**Head Major Diameter:**

0.243 inches

**Expansion Device:**

Plain stem-type t

**Grip Length:**

Between 0.063 inches and 0.125 inches

**Countersink Angle:**

120.0 degrees

**Material:**

Steel comp 1030 mandrel or steel comp 1033 mandrel or steel comp 1034 mandrel or steel comp 1035 mandrel or steel comp 1536 mandrel or steel comp 1037 mandrel or steel comp 1038 mandrel or steel comp 1039 mandrel or steel comp 1040 mandrel or steel comp 1541 mandrel or steel comp 1042 mandrel or steel comp 1043 mandrel or steel comp 1044 mandrel or steel comp 1045 mandrel or steel comp 1046 mandrel or steel comp 1548 mandrel or steel comp 1049 mandrel or steel comp 1050 mandrel or steel comp 1551 mandrel or steel comp 1552 mandrel or steel comp 1053 mandrel or steel comp 1055 mandrel or steel comp 1059 mandrel or steel comp 1060 mandrel

**Material Specification:**

66 federal standard all material responses mandrel

**Surface Treatment:**

Zinc mandrel or chromate mandrel or phosphate mandrel

**Surface Treatment Specification:**

Qq-z-325 type 2 cl 3 federal specification 1st treatment response mandrel or qq-p-416 federal specification 2nd treatment response mandrel or mil-p-16232 ty z cl 2 military specification 3rd treatment response mandrel or mil-p-16232 ty z cl 4 military specification 3rd treatment response mandrel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-p-162232 spec.