## NSN 5320-01-053-7550



Pin-rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-053-7550 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.411 inches and 1.431 inches **Head Style:** Err-090 **Head Height:** Between 0.070 inches and 0.078 inches Width Between Flats: Between 0.127 inches and 0.129 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.483 inches and 0.503 inches **Grip Length:** Between 0.939 inches and 1.000 inches **Thread Size:** 0.312 inches **Special Features:** Mechanical lock feature on threads, hole through threaded portion of shank with diameter of 0.076 in. Min and 0.086 in. Maximum and 0.230 in. From end Material: Steel comp 8740 or steel comp 4340 **Material Specification:** Aisi8740 assn standard single material response or aisi4340 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No Fiig:

A528u0

**Demilitarization:**