## NSN 5320-01-054-5997

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-054-5997

| Fastener Length:   |
|--|
| Between 1.396 inches and 1.416 inches  |
| Head Style:  |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)                                   |
| Shank Diameter:  |
| Between 0.186 inches and 0.190 inches  |
| Shank Style:   |
| Straight w/radius chamfered tip  |
| Head Major Diameter:   |
| 0.357 inches   |
| Shear Strength:  |
| 26000 single pounds per square inch  |
| Countersink Angle:   |
| 100.0 degrees  |
| Heat Treatment:  |
| T-4 solution heat treated  |
| Material:  |
| Aluminum alloy 2117  |
| Material Specification:  |
| Qq-a-430 federal specification single material response  |
| Surface Treatment:   |
| Anodize or chromate  |
| Surface Treatment Specification:   |
| Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |
| Mil-std (military Standard):   |
| Mil-a-8625 spec.   |