
NSN 5320-01-054-8433

Pin-rivet - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.302 inches and 1.317 inches

Head Style:

Flush countersunk

Head Height:

0.104 inches

Shank Diameter:

Between 0.263 inches and 0.265 inches

Shank Style:

Err-090

Head Major Diameter:

0.507 inches

Grip Length:

Between 1.501 inches and 1.562 inches

Thready Qty Per Inch (tpi):

48

Thread Size:

0.217 inches

Countersink Angle:

100.0 degrees

Special Features:

Collar w/ 0.213 in. Min to 0.216 in. Maximum id and 0.256 in. Min to 0.262 in. Maximum od and 0.060 in. Min to 0.070 in. Maximum width w/

0.094 in. Hex socket in rivet head

Material:

Steel body

Material Specification:

Fed standard 66, aisi/sae 8740 federal specification 1st material response body

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5320-01-054-8433

Pin-rivet - Page 2 of 2

Fiig: A528u0

