

View Online at <https://aerobasegroup.com/nsn/5320-01-054-9712>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.928 inches and 0.943 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.263 inches and 0.265 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

0.507 inches

**Grip Length:**

Between 1.189 inches and 1.250 inches

**Thready Qty Per Inch (tpi):**

48

**Thread Size:**

0.217 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Designed to mate w/collar 0.216 in. Maximum id and 0.262 in. Od and 0.070 in. Maximum width: rivet head has 0.094 in. Hexagonal socket: end item f16: used on f16 lh wing box

**Material:**

Steel comp 8740 sleeve

**Material Specification:**

Qq-a-430 federal specification 2nd material response collar

**Surface Treatment:**

Cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification 1st treatment response sleeve

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.