

View Online at <https://aerobasegroup.com/nsn/5320-01-054-9712>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.928 inches and 0.943 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.263 inches and 0.265 inches

Shank Style:

Err-090

Head Major Diameter:

0.507 inches

Grip Length:

Between 1.189 inches and 1.250 inches

Thready Qty Per Inch (tpi):

48

Thread Size:

0.217 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Designed to mate w/collar 0.216 in. Maximum id and 0.262 in. Od and 0.070 in. Maximum width: rivet head has 0.094 in. Hexagonal socket: end item f16: used on f16 lh wing box

Material:

Steel comp 8740 sleeve

Material Specification:

Qq-a-430 federal specification 2nd material response collar

Surface Treatment:

Cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification 1st treatment response sleeve

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.