

View Online at <https://aerobasegroup.com/nsn/5320-01-054-9713>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.062 inches

**Head Style:**

Flush countersunk

**Head Height:**

0.104 inches

**Shank Diameter:**

Between 0.263 inches and 0.265 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

0.507 inches

**Grip Length:**

Between 1.251 inches and 1.312 inches

**Thready Qty Per Inch (tpi):**

48

**Thread Size:**

0.217 inches

**Countersink Angle:**

100.0 degrees

**Special Features:**

Designed to mate w/ collar 0.216 in. Maximum id and 0.262 in. Od and 0.070 in. Maximum width w/ matl aluminum alloy, 2219-t6, rivet head has 0.094 in. Hexagonal socket

**Material:**

Steel comp 8740 sleeve

**Material Specification:**

Qq-a-430 federal specification 2nd material response collar

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.