NSN 5320-01-055-6201

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-055-6201



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.052 inches and 1.067 inches

Head Style:

Flush countersunk

Head Height:

0.104 inches

Shank Diameter:

Between 0.263 inches and 0.265 inches

Shank Style:

Err-090

Head Major Diameter:

0.507 inches

Grip Length:

Between 1.313 inches and 1.375 inches

Thready Qty Per Inch (tpi):

48

Thread Size:

0.217 inches

Countersink Angle:

100.0 degrees

Special Features:

Designed to mate w/ collar 0.216 in. Maximum id and 0.262 in. Od and 0.070 in. Maximum width w/ matl aluminum alloy, 2219-t6, rivet head has 0.094 in. Hexagonal socket

Material:

Steel comp 8740 sleeve

Material Specification:

Qq-a-430 federal specification 2nd material response collar

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5320-01-055-6201

Pin-rivet - Page 2 of 2

Fiig: A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

