

View Online at <https://aerobasegroup.com/nsn/5320-01-055-6813>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.052 inches and 0.075 inches

**Head Style:**

Flush countersunk

**Head Height:**

0.078 inches

**Shank Diameter:**

Between 0.200 inches and 0.202 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

0.386 inches

**Grip Length:**

Between 0.251 inches and 0.312 inches

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.164 inches

**Countersink Angle:**

100.0 degrees

**Special Features:**

Rivet head has 0.078 in. Hexagonal socket, rivet designed to mate w/lock collar od 0.195 in. Min 0.200 in. Max, lock collar surface treatment per mil-c-5541, sleeve lubricated w/cetyl alcohol

**Material:**

Steel body

**Material Specification:**

Fed standard 66, aisi/sae 8740 federal specification 1st material response body

**Surface Treatment:**

Cadmium body

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response body

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0