

View Online at <https://aerobasegroup.com/nsn/5320-01-056-1563>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.445 inches and 0.485 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.039 inches and 0.047 inches

**Width Between Flats:**

Between 0.0635 inches and 0.0645 inches

**Shank Diameter:**

Between 0.1625 inches and 0.1635 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.245 inches and 0.257 inches

**Grip Length:**

Between 0.178 inches and 0.198 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Material:**

Steel comp 8740 or steel comp e4340 or steel comp 4340

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5000 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas4450 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.