# NSN 5320-01-057-3198

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-057-3198



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.536 inches and 0.556 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.061 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.398 inches and 0.413 inches

#### Grip Length:

Between 0.126 inches and 0.188 inches

## Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Chlorine free cetyl alcohol lubrication

#### Material:

Titanium alloy

#### Material Specification:

Ams 4967 assn standard single material response

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas4450 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-057-3198

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

