# NSN 5320-01-057-8234

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.723 inches and 0.743 inches

## Head Style:

Flush countersunk

# Width Between Flats:

Between 0.0947 inches and 0.0967 inches

# Shank Diameter:

Between 0.2485 inches and 0.2495 inches

## Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

0.399 inches

Grip Length:

Between 0.313 inches and 0.375 inches

# Thready Qty Per Inch (tpi):

28

# Thread Size:

0.250 inches

# Shear Strength:

156000 single pounds per square inch

## **Countersink Angle:**

100.0 degrees

Material:

Steel comp h11

## **Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

## **Surface Treatment Specification:**

Ams 2416 assn standard all treatment responses

## **Thread Series Designator:**

Unjf

# **Specification Data:**

80205-nas4452 professional/industrial association standard

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-057-8234

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

