

View Online at <https://aerobasegroup.com/nsn/5320-01-057-9379>

Fastener Length:

0.662 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.186 inches and 0.190 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.357 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film

Grip Length:

Between 0.438 inches and 0.500 inches

Min. Tensile Strength (psi):

95000 pounds per square inch

Shear Strength:

2260 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Rivet may be slosch cleaned with mil-c-38736 cleaner before installation

Material:

Nickel alloy 400 sleeve or nickel alloy r-405 sleeve

Material Specification:

Qq-n-281 federal specification all material responses sleeve

Surface Treatment:

Passivate locking ring

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification 1st treatment response sleeve or nas 4006 assn standard 2nd treatment response sleeve

Specification Data:

80205-nas1921 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0