NSN 5320-01-057-9388

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-057-9388



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.410 inches and 0.430 inches

Head Style:

Err-090

Head Height:

Between 0.042 inches and 0.050 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.298 inches and 0.312 inches

Grip Length:

Between 0.063 inches and 0.125 inches

Thready Qty Per Inch (tpi):

37

Thread Size:

0.190 inches

Shear Strength:

156000 single pounds per square inch

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or aams 6487 assn standard all material responses

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas4450 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-01-057-9388

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

