# NSN 5320-01-058-0822

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-058-0822

# Fastener Length:

0.678 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.197 inches and 0.199 inches

## Shank Style:

Self-plugging mechanically locked stem

## Head Major Diameter:

0.386 inches

Expansion Device:

Serrated stem-type w

## Grip Length:

Between 0.469 inches and 0.532 inches

## Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

#### Shear Strength:

3450 single pounds per square inch

#### Countersink Angle:

100.0 degrees

## **Special Features:**

Installed with single action tool

### Material:

Steel comp 8740 stem

### **Material Specification:**

Astm a547 assn standard single material response stem or mil-s-6049 military specification single material response stem

### Surface Treatment:

Cadmium stem

### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

#### Shelf Life:

N/a

## Unit Of Measure:

```
--
```

### Demilitarization:

No

# Fiig:

A040a0

## Mil-std (military Standard):

Mil-s-6758 spec.