
# NSN 5320-01-058-0832

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.786 inches and 0.806 inches

#### Head Style:

Flush countersunk

## Width Between Flats:

Between 0.1270 inches and 0.1295 inches

## Shank Diameter:

Between 0.3110 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.492 inches

# Grip Length:

Between 0.313 inches and 0.375 inches

# Thready Qty Per Inch (tpi):

24

## Thread Size:

0.312 inches

## Shear Strength:

156000 single pounds per square inch

## **Countersink Angle:**

100.0 degrees

#### Material:

Steel comp h11

## **Material Specification:**

Ams 6485 assn standard single material response or ams6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

## Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

#### **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas4452 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 5320-01-058-0832

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

