

View Online at <https://aerobasegroup.com/nsn/5320-01-058-4112>

**Fastener Length:**

0.537 inches

**Head Style:**

Universal

**Head Height:**

Between 0.080 inches and 0.090 inches

**Shank Diameter:**

Between 0.186 inches and 0.190 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.356 inches and 0.394 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film

**Grip Length:**

Between 0.313 inches and 0.375 inches

**Shear Strength:**

2260 single pounds per square inch

**Special Features:**

Rivet may be slosch cleaned with mil-c-38736 cleaner before installation

**Material:**

Nickel alloy 400 sleeve or nickel alloy r-405 sleeve

**Material Specification:**

Qq-n-281 federal specification all material responses sleeve

**Surface Treatment:**

Passivate stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response sleeve or nas 4006 assn standard 2nd treatment response sleeve

**Specification Data:**

80205-nas1919 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0