NSN 5320-01-058-4713

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-058-4713



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.573 inches and 0.593 inches

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.193 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

294, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-01-058-4713

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

