
# NSN 5320-01-058-5437

Pin-rivet - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.565 inches and 0.585 inches

# Head Style:

Err-090

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

## Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

#### 0.303 inches

Lubrication:

Cetyl alcohol

# Grip Length:

0.255 inches

# Thready Qty Per Inch (tpi):

32

# Thread Size:

0.190 inches

## Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Titanium alloy

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

# Surface Treatment Specification:

294, fscm 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-058-5437

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

