# NSN 5320-01-058-8474

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-058-8474

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.573 inches and 0.593 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

#### Head Major Diameter:

#### 0.3948 inches

Lubrication:

Cetyl alcohol

### Grip Length:

0.193 inches

#### Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Titanium alloy

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

294, fscm 73197 mfr ref single treatment response

### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

### Unit Of Measure:

--

# NSN 5320-01-058-8474

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

