## NSN 5320-01-058-8476

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-058-8476 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.885 inches and 0.905 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.3948 inches Lubrication: Cetyl alcohol **Grip Length:** 0.505 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-058-8476

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0