# NSN 5320-01-058-8480

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-058-8480



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.885 inches and 0.905 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.415 inches and 0.440 inches

### Lubrication:

Cetyl alcohol

## Grip Length:

0.505 inches

## Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.250 inches

# Shear Strength:

95000 single pounds per square inch

## Material:

Titanium alloy

# Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# Surface Treatment:

Aluminum

# Surface Treatment Specification:

294, fscm 73197 mfr ref single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-058-8480

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

