# NSN 5320-01-059-0333

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.635 inches and 0.655 inches

## Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

## Width Between Flats:

Between 0.0947 inches and 0.0967 inches

## Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Head Major Diameter:

Between 0.415 inches and 0.440 inches

# Lubrication:

Cetyl alcohol

# Grip Length:

0.255 inches

# Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

160000 pounds per square inch

# Thread Size:

0.250 inches

## Shear Strength:

95000 single pounds per square inch

## Material:

Titanium alloy

## Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Surface Treatment:

Aluminum

# Surface Treatment Specification:

294, fscm 73197 mfr ref single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a



# NSN 5320-01-059-0333

Pin-rivet - Page 2 of 2



---

Demilitarization:

No

Fiig:

A528u0

