

View Online at <https://aerobasegroup.com/nsn/5320-01-059-1991>

**Fastener Length:**

1.053 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.197 inches and 0.199 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.386 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.844 inches and 0.907 inches

**Hardness Rating:**

48.0 rockwell c stem and 53.0 rockwell c stem

**Shear Strength:**

3450 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Installed with single action tool

**Material:**

Steel comp 8740 stem

**Material Specification:**

66 federal standard 1st material response sleeve or astm a547 assn standard 2nd material response sleeve or mil-s6758mdcl2apjgaastm a547 military specification 3rd material response sleeve or mil-s-6049 military specification single material response sleeve

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6049 spec.