

View Online at <https://aerobasegroup.com/nsn/5320-01-059-1991>

Fastener Length:

1.053 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.386 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.844 inches and 0.907 inches

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

Shear Strength:

3450 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Installed with single action tool

Material:

Steel comp 8740 stem

Material Specification:

66 federal standard 1st material response sleeve or astm a547 assn standard 2nd material response sleeve or mil-s6758mdcl2apjgaastm a547 military specification 3rd material response sleeve or mil-s-6049 military specification single material response sleeve

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.