

View Online at <https://aerobasegroup.com/nsn/5320-01-059-1993>

Fastener Length:

0.600 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.186 inches and 0.190 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.357 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film

Grip Length:

Between 0.376 inches and 0.437 inches

Shear Strength:

1090 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Rivet may be slosh cleaned with mil-c-38736 cleaner before installation

Material:

Aluminum alloy 5056 sleeve

Material Specification:

Qq-a-430 federal specification single material response stem

Surface Treatment:

Anodize stem or chromate stem

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

Specification Data:

80205-nas1921 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.